

AISIN

TECHNICAL DATA SHEET

CVT FLUID

ATF-SCV

ATF-SCV is formulated for Subaru & Mitsubishi Transmissions that require CVTF-II & CVTF-J4 Fluid.



(Color: **Green**)

12 BOTTLES PER CASE	VIO US: 1.6M
BARCODE-EACH	0030915583152
BARCODE-CASE	0030915589987
WEIGHT-CASE	23.8 LBS
REPLACES Subaru P/N	SOA427V1650
	SOA427V1660
REPLACES Mitsubishi P/N	MZ320806

CERTIFICATE OF ANALYSIS

Synthetic Automatic Transmission Fluid				
Product Name	AISIN Synthetic ATF-SCV Formulated for CVTF-II & J4 Application.			
TEST	METHODS	SPECIFICATIONS	RESULTS	UNITS
Appearance	Visual	Clear	Clear	
Color	Visual	Green	Green	
Density °C	ASTM D4052	≥ 0.8000	0.85	g/cm ³
Flash Point – COC	ASTM D92	≥ 180	206	°C
Kinematic Viscosity 40°C	ASTM D445	≤ 30.5	29.4	mm ² /s
Kinematic Viscosity 100°C	ASTM D445	≥ 6.35	6.45	mm ² /s
Viscosity Index	ASTM D2270	≥ 175	182	
Pour Point	ASTM D97	≤ -39	-45	°C
Total Base Number (HClO ₄)	ASTM D2896	≥ 2.8	3.1	mgKOH/g
Foaming SEQ II	ASTM D892	≤ 50 / 0	10 / 0	mL/mL
Water Content	ASTM D6304	≤ 600	202	mass ppm
Elemental Analysis – Ca	ASTM D4951	0.033 – 0.048	0.040	mass %
Elemental Analysis – P	ASTM D4951	0.050 – 0.070	0.058	mass %
Elemental Analysis – S	ASTM D4951	0.2000 – 0.300	0.279	mass %

For additional details and application information, please review the data provided by AISIN, or your catalog provider or visit us on our website: www.aisinaftermarket.com Please contact your AISIN sales representative for additional information.