

AISIN

TECHNICAL DATA SHEET

Automatic Transmission Fluid

ATF-SHP

ATF-SHP is formulated for Subaru Transmissions that require HP Fluid.



(Color: **RED**)

12 BOTTLES PER CASE	VIO US: 1.4M
BARCODE-EACH	0703205766930
BARCODE-CASE	0703205767227
WEIGHT-CASE	23.8 LBS
REPLACES Subaru P/N	SOA427V1500

Certificate of Analysis

Synthetic Automatic Transmission Fluid				
Product Name	AISIN Synthetic ATF-SHP Formulated for TYPE SHP.			
TEST	METHODS	SPECIFICATIONS	RESULTS	UNITS
Appearance	Visual	Clear	Clear	
Color	Visual	Red	Red	
Density °C	ASTM D4052	≥ 0.84	0.8495	g/cm ³
Flash Point – COC	ASTM D92	≥ 175	222	°C
Kinematic Viscosity 40°C	ASTM D445	30.0 – 39.0	34.8	mm ² /s
Kinematic Viscosity 100°C	ASTM D445	≥ 7.0	7.16	mm ² /s
Viscosity Index	ASTM D2270	≥ 170	175	
Pour Point	ASTM D97, D5950	≤ -39	-51	°C
Total Base Number (HClO ₄)	ASTM D2896	Report	4.5	mgKOH/g
Foaming SEQ II	ASTM D892	≤ 50 / 0	10 / 0	mL/mL
Elemental Analysis – B	ASTM D4951	Report	51.7	mass ppm
Elemental Analysis – Ca	ASTM D4951	60 – 180	118	mass ppm
Elemental Analysis – P	ASTM D4951	270 – 400	339	mass ppm

For additional details and application information, please review the data provided by AISIN, or your catalog provider or visit us on our website: www.aisinaftermarket.com Please contact your AISIN sales representative for additional information.