

AISIN

TECHNICAL DATA SHEET

CVT FLUID

ATF-TFE

ATF-TFE is formulated for Lexus/Scion/Toyota Transmissions that require FE Continuously Variable Transmission Fluid.



(Color: Red)

12 BOTTLES PER CASE	VIO US: 1.6M
BARCODE-EACH	0030915589932
BARCODE-CASE	0030915589956
WEIGHT-CASE	23.8 LBS
REPLACES TOYOTA P/N	08886-02505

CERTIFICATE OF ANALYSIS

Synthetic Automatic Transmission Fluid				
Product Name		AISIN Synthetic ATF-TFE Formulated for Toyota CVT-FE Applications.		
TEST	METHODS	SPECIFICATIONS	RESULTS	UNITS
Appearance	Visual	Clear	Clear	
Color	Visual	Red	Red	
Density °C	ASTM D4052	≥ 0.8000	0.85	g/cm ³
Flash Point – COC	ASTM D92	≥ 180	204	°C
Kinematic Viscosity 40°C	ASTM D445	≤ 30.5	29.9	mm ² /s
Kinematic Viscosity 100°C	ASTM D445	≥ 6.35	6.56	mm ² /s
Viscosity Index	ASTM D2270	≥ 175	184	
Pour Point	ASTM D97	≤ -39	-45	°C
Total Base Number (HClO ₄)	ASTM D2896	≥ 2.8	3.2	mgKOH/g
Foaming SEQ II	ASTM D892	≤ 50 / 0	10 / 0	mL/mL
Water Content	ASTM D6304	≤ 600	209	mass ppm
Elemental Analysis – Ca	ASTM D4951	0.033 – 0.048	0.038	mass %
Elemental Analysis – P	ASTM D4951	0.050 – 0.070	0.057	mass %
Elemental Analysis – S	ASTM D4951	0.2000 – 0.300	0.250	mass %

For additional details and application information, please review the data provided by AISIN, or your catalog provider or visit us on our website: www.aisinaftermarket.com Please contact your AISIN sales representative for additional information.